



E-BIKES COMPARISON







CENTRE MOTOR

- · Battery integrated into frame
- Central 250W Brose motor (Made in Germany) with triple
- · Assistance up to 25 km/h and accelerator up to 6 km/h
- Q factor standard
- Standard transmission with possibility for double plate or internal gearshift
- · Approved as an electrical bicycle (EN15914)
- Maximum assistance from 1 (user torque) to 3.3 (Motor toque)
- Central Brose motor with efficiency from 75 to 82%
- Maximum torque of 90 Nm
- · Resistance free motor in non-assistance mode

- Battery in front triangle
- Central 250W Yamaha motor with triple sensor
- Assistance up to 25 km/h and accelerator up to 6 km/h
- Transmission with possibility for double plate or internal
- Approved as an electrical bicycle (EN15914)
- Maximum assistance from 1 (user torque) to 3 (Motor toque)
- Central high efficiency Yamaha motor (PW-X, PW)
- . Maximum torque of 80 Nm
- · Resistance free motor in non-assistance mode

- Battery in front triangle or in the mesh.
- Central 250W Bosch motor with triple sensor
- · Assistance up to 25 km/h and accelerator up to 6 km/h
- . Approved as an electrical bicycle (EN15914)

- Maximum assistance from 1 (user torque) to 3 (Motor torque Performance CXX
- · Central high efficiency Bosch motor
- Maximum torque of 75 Nm
- · Resistance free motor in non-assistance mode

• 400W (Lite), 500Wh (Standard), and 600Wh (Pro) Lithium-lon battery integrated into the frame.

- Allows up to 125 km autonomy (Pro 500Wh battery) and 105 km (Standard 500Wh battery), and 85 km (Lite 400Wh battery) in Mixed mode in ideal conditions
- Useful life 20% maximum deterioration after 500 complete recharging cycles. > 30.000 Km.
- Automatic protection for periods of non-usage (Automatic Care System)
- · Compact and removable Central LCD screen (Pro models) or Lateral compact and removable LCD screen (Standard and Lite models)
- Multifunction display with information about autonomy, distance, speed, time, assistance, etc.
- · Diagnostics Kit
- GPS Tracker Module (supplied from the main battery)
- BT Module and Premium Application (IOS and Android)
- · Winter Cover for Battery
- Lights Kit

- Yamaha Ion Lithium-Ion battery for 400Wh (Lite) and 500Wh (Standard)
- Allows up to 105 km autonomy (Standard 500Wh battery) and 85 km (Lite 400Wh battery), in the Mixed mode in ideal conditions
- Useful life 20% maximum deterioration after 500 complete recharging cycles. > 30.000 Km.
- · Automatic protection for periods of non-usage
- Compact and removable central LCD Yamaha screen
- · Multifunction display with information about autonomy, distance, speed, time, assistance, etc.
- The Display Yamaha PW-X has Bluetooth connectivity that allows connecting the system with sports applications like Strava or Runtastic.

- Yamaha Ion Lithium-Ion Powerpack for 400Wh (Lite) and 500Wh (Standard)
- Allows up to 105 km autonomy (Standard 500Wh battery) and 85 km (Lite 400Wh battery), in the Mixed mode in ideal
- Useful life 20% maximum deterioration after 500 complete recharging cycles. > 30.000 Km.
- · Automatic protection for periods of non-usage
- Compact and removable central LCD Intuvia screen
- · Multifunction display with information about autonomy, distance, speed, time, assistance, etc.

BATTERY

OPTIONAL KITS

COMPARISON E-BIKES







REAR MOTOR

AWD: DOUBLE MOTOR

- · Battery completely integrated into frame
- Rear 350W and 48V high performance motor with integrated thru axle
 - AWD: Additional forward motor of 250W
- Assistance up to 25 km/h and accelerator up to 6 km/h
 - AWD: Assistance up to35 km/h and accelerator up to 6 km/h
- 0 factor standard
- Standard transmission with possibility for double or triple plate
- Approved as an electrical bicycle (EN15914)
- Maximum assistance from 1 (user torque) to 3.75 (Motor toque)
 - AWD: Maximum assistance from 1 (user torque) to 4 (Motor toque)
- Rear 350W and 48V motor with 84 to 91% efficiency
 - AWD: In addition, front 250W motor with 75 to 91% efficiency
- Peak performance of 650W
 - AWD: Peak performance of 432W in front motor
- Resistance free motor in non-assistance mode
- 400W (Lite), 500Wh (Standard), and **600Wh (Pro and AWD)** Lithium-lon battery integrated into the frame.
- Allows up to 125 km autonomy (Pro 500Wh battery) and 105 km (Standard 500Wh battery), and 85 km (Lite 400Wh battery) in Mixed mode in ideal conditions.
- Useful life 20% maximum deterioration after 500 complete recharging cycles. > 30.000 Km.
- Automatic protection for periods of non-usage (Automatic Care System)
- Compact and removable Central LCD screen (Pro and AWD models) or Lateral compact and removable LCD screen (Standard and Lite)
- Multifunction display with information about autonomy, distance, speed, time, assistance, etc.
- Diagnostics Kit
- GPS Tracker Module (supplied from the main battery)
- BT Module and Premium Application (IOS and Android)
- Winter Cover for Battery
- Lights Kit

- Battery completely integrated into frame
- Rear 500W and 48V high performance motor with integrated thru axle
- Assistance up to 45 km/h and accelerator up to 20 km/h
- Q factor standard
- Standard transmission with possibility for double or triple plate
- Homologated as L1 e motorcycle
- Maximum assistance from 1 (user torque) to 3.75 (Motor toque)
- Rear 500W and 48V motor with 82 to 88% efficiency
- Peak performance of 760W
- Resistance free motor in non-assistance mode

- · Sliding battery on seat post support
- Rear 250W high performance motor with integrated thru axle
- Assistance up to 25 km/h and accelerator up to 6 km/h
- Q factor standard
- Standard transmission with possibility for double or triple plate
- Approved as an electrical bicycle (EN15914)
- Maximum assistance from 1 (user torque) to 3 (Motor toque)
- Rear 250W motor with 75 to 82% efficiency
- Peak performance of 432W
- Resistance free motor in non-assistance mode
- 600Wh (Pro) Lithium-lon battery integrated into the frame.
- Autonomy up to 85 km under Mixed mode in favourable conditions
- Useful life 20% maximum deterioration after 500 complete recharging cycles. > 30.000 Km.
- Automatic protection for periods of non-usage (Automatic Care System)
- Compact and removable central LCD screen
- Multifunction display with information about autonomy, distance, speed, time, assistance, etc.

- 250W Ion Lithium-Ion battery in the seat post
- Autonomy up to 50 km under Mixed mode in favourable conditions
- Useful life 20% maximum deterioration after 500 complete recharging cycles. > 30.000 Km.
- Automatic protection for periods of non-usage (Automatic Care System)
- Compact and removable lateral LCD screen
 - Multifunction display with information about autonomy, distance, speed, time, assistance, etc.

- Diagnostics Kit
- GPS Tracker Module (supplied from the main battery)
- BT Module and Premium Application (IOS and Android)
- Winter Cover for Battery

- Diagnostics Kit
- Battery blocking lock







USB connection





Bluetooth KIT & BH Bikes Premium APP

Nitro, Revo, Evo, Evo AWD, EasyGo

Its new design and new functions incorporate improved connectivity and usability. User experience during use has been improved in order to have its own controls and a much more personalized version.

- More than 40 measurable parameters (speed, distance, calories, elevation, power, etc).
- Customizable screen: Topographic profile / navigation map / virtual competitor.
- 3 riding types: manual, intelligent based on topography and intelligent based on heart beat.
- GPS navigation with intermediate points.
- File of route.
- System check (Battery wear status, calibration of torque sensor and identification of errors and operational protocol.

- Motor selection (Only EVO AWD models)
- Integration with Strava; It connects the application your Strava profile and uploads trips with complete information.
- Compares your saved routes You can compete against yourself and exceed your records in each route.
- Navigate to selected point with automatic assistance regulation in distance, ascents and descents and battery charge.
- It automatically regulates the bikes based on your heart frequency - BT Smart connectivity.
- It adapts the assistance, battery and motor configuration based on your needs - Including AWD mode.




GPS tracker

Nitro, Revo, Evo, Evo AWD

The GPS Tracker optional mode is the perfect anti-theft system It allows locating the bicycle at any time by the user. Its perfect integration into the bicycle makes it accessible for the user and its control through Web and Premium applications allow its easy configuration. Among its functions, we highlight:

- Location of the bicycle with 10 metres precision (in the open-air using GPS).
- Bicycle route tracking configuring a connection frequency.
- Weak battery, Geoforce, or connection type alarm.
- Continuous power supply from the bicycle battery allowing longlasting autonomy (once the main battery reaches 10% its power supply stops).



Diagnostics KIT

It allows complete revision of the bicycle electrical system and in the case of problems; it identifies the specific location of the defective part for replacement.

Likewise it allows changing the performance parameters of the system regarding the mode provide torque, motor reactivity or acceleration speed.



Winter cover

Nitro, Revo, Evo, Evo AWD

The optional winter battery-cover kit with a 5 mm layer of Neoprene keeps the battery heat, that way increasing its performance and allowing the user up to 15% more autonomy in extremely low temperatures (<10 °C).



Lights KIT

Revo, Evo, Evo AWD

The optional lights kit allows connecting standard 6V lights to the system, controlling them from the screen (or Premium application).



Blockage lock

EasyGo

The optional lock for EASYGO battery blockage fixes the battery to its support.



Drop Out adaptor for Kickstand

Evo

E-BIKES REVO

REVO

Center LCD Emotion Lateral LCD Emotion LCD 600Wh

500Wh 400Wh

d 44 250W

Up to 125 Km Up to 105 Km Up to 85 Km

Upgradekits

Bluetooth kit + Premium App GPS Tracker Winter Battery Cover Light cable



REVO LYNX 4.8 27,5" PRO **ER907**

120 mm Full Suspension Alloy 27'5" internal cable routing FOX FLOAT DPS

FOX FLUAL D. D. Performance FOX 34 FLOAT Rhythm 120mm 150R

FSA 36T

() Shimano SLX

Schwalbe Tough Tom 27,5"x2,35

4 600Wh

MD/LA

kg 23,6

REVO 27,5" PLUS PRO **ER747**

MTB Alloy 27,5"+

internal cable routing FOX 32 FLOAT Perfor mance 100mm 15QR

🕏 Shimano XT 11sp

() Shimano SLX

C Schwalbe Nobby Nic 27,5+x2,8

600Wh

MD/LA

kg 22,1



REVO LYNX 6 27'5" PRO **ER947**

160 mm Full Suspension Alloy 27'5" internal cable routing FOX FLOAT DPS FOX FLOAT DI C Performance FOX 36 FLOAT Performance 160mm 150R

(Shimano SLX

Schwalbe Tough Tom 27,5"x2,35

4 600Wh

MD/LA

kg 23,6



REVO BIG BUD PRO

ER807

Fat Bike Alloy 26" internal

cable routing Rock Shox Bluto 100mm 15QR

7 Shimano XT 10sp

FSA 36T

(Shimano M396)

Emotion 26"x4,0

600Wh

kg 24,2

COMPATIBLE 27,5" PLUS

(Shimano M396)

REVO 29" ER727

MTB Alloy 29" internal cable routing

Rock Shox 30S 100mm

C Schwalbe Rapid Rob 29"x2,25

Shimano XT 10sp

■ 500Wh

MD/LA

kg 22,1

FSA 38/24T

REVO E-BIKES 1



REVO 29" LITE ER707

- MTB Alloy 29" internal cable routing
- ★ SR Suntour XCT HLO
- Shimano Deore 10sp
- SFSA 36T
- (Shimano M315) Kenda Honey Badger 29"x2,25
- 400Wh



MD/LA



REVO 27,5" PRO **ER647**

- MTB Alloy 27,5" internal
- cable routing FOX 32 FLOAT Perfor-mance 100mm 15QR
- Shimano XT 11sp
- (S) Shimano SLX
- Schwalbe Racing Ralph 27,5"x2,25
- **■** 600Wh

SM/MD/LA kg 22,0



REV0 27,5"

ER627

- MTB Alloy 27,5" internal cable routing
- Rock Shox 30S 100mm
- 7 Shimano XT 10sp

- Schwalbe Rapid Rob 27'5"x2,25
- 500Wh
- (S) Shimano M396 SM/MD/LA
 - kg 22,0





- MTB Alloy 27,5" internal
- cable routing ★ SR Suntour XCT HLO
- Shimano Deore 10sp
- FSA 36T
- (Shimano M315)
- Kenda Honey Badger 27'5"*2,25
- 400Wh

MD/LA

kg 22,0



REVO JET PRO **ER557**

- Sport Hybrid Alloy 28" internal cable routing SR Suntour NCX–D LO Lite
- \$\frac{1}{8}\$ Shimano XT 10sp
- FSA 42/28T
- (Shimano SLX)
 - Schwalbe Big Apple 28"x2,0
 - **₫** 600Wh
- kg 22,7

MD/LA

- REVO CROSS PRO **ER547**
- Sport Alloy 28" internal cable routing SR Suntour NCX–D LO Lite

 - \$\frac{1}{8}\$ Shimano XT 10sp
- (Shimano SLX)
- Schwalbe Big Apple 28"x2,0
- 600Wh





E-BIKES REVO



REVO JET

ER537

Sport Hybrid Alloy 28" internal cable routing

SR Suntour NEX HLO

7 Shimano XT 10sp

FSA 42/28T

(D) Shimano M396

Schwalbe Big Apple 28"x2,0

□ 500Wh

MD/LA

kg 22,7

REVO CROSS

ER527

Sport Alloy 28" internal cable routing

SR Suntour NEX HLO

Shimano XT 10sp

FSA 42/28T

(Shimano M396

Schwalbe Big Apple 28"x2,0

kg 22,8

■500Wh

SM/MD/LA



REVO JET LITE **ER517**

Sport Hybrid Alloy 28" internal cable routing

🕏 Shimano Deore 10sp

SR Suntour NVX

(Shimano M315)

(Kenda K192 28"x1,75

kg 22,7

400Wh

MD/LA



Sport Alloy 28" internal cable routing

SR Suntour NVX

7 Shimano Deore 10sp

FSA 38T

(E) Shimano M315

Kenda K192 28"x1,75

400Wh

MD/LA

kg 22,8



REVO DIAMOND WAVE PRO **ER457**

City Wave Alloy 28" internal cable routing

SR Suntour CR8V HLO

Nuvinci M360

(S) Magura Hydraulic HS-11 MD / LA

C Schwalbe Marathon 700x38C

€ 600Wh

kg 26,8

REVO DIAMOND WAVE

ER417

City Wave Alloy 28" internal cable routing

SR Suntour CR8V HL0

Shimano Nexus 8sp

(S) Magura Hydraulic HS-11 MD / LA


Schwalbe Marathon 700x38C

■ 500Wh

kg 25,3



REVO E-BIKES 1





REBEL





500Wh 400Wh

44

250W

Up to 105 Km Up to 85 Km

LCD Yamaha

25 Km/h

Upgrade kits



REBEL LYNX 5.5 27,5" PLUS PW-X

EY987

140 mm Full Suspension Alloy 27,5"+ internal cable routing FOX FLOAT DPS FOX FLUAL D. Performance
FOX 34 FLOAT Rhythm
140mm 150R

(Shimano SLX

Schwalbe Nobby Nic 27,5" PLUSx3

500Wh

MD/LA

kg 21,8



REBEL LYNX 5.5 29" **EY967**



140 mm Full Suspension Alloy 29" internal cable routing

Rock Shox Monarch

Rock Shox Sektor 140mm 15QR

7 Shimano XT 11sp

B FSA 36T

() Shimano SLX

Schwalbe Rapid Rob

500Wh



REBEL LYNX 5.5 27,5"

EY907

140 mm Full Suspension Alloy 27,5" internal cable routing

Rock Shox Monarch

Rock Shox Sektor 140mm 15QR Shimano XT 11sp () Shimano SLX

Schwalbe Rapid Rob 27'5"x2,25

■500Wh

MD/LA kg 22,3



REBEL 27,5" PLUS PW-X **EY747**

MTB Alloy 27'5+ internal cable

routing FOX 32 FLOAT Performance 100mm 15QR

Shimano XT 11sp

() Shimano SLX

C Schwalbe Nobby Nic 27,5PLUSx2,8

■500Wh

MD/LA kg 22,1

111 MD

kg 22,8



REBEL 29"

EY727

MTB Alloy 29" internal cable routing

Rock Shox 30S 100mm

7 Shimano XT 10sp

FSA 38/24T

(Shimano M396)

Schwalbe Rapid Rob 29"x2,25

□ 500Wh

MD/LA kg 21,7

REBEL E-BIKES 1

BH.17



REBEL 29" LITE **EY707**

MTB Alloy 29" internal cable routing

★ SR Suntour XCT HLO

Shimano Deore 10sp

SFSA 36T

(Shimano M315)

Kenda Honey Badger 29"*2,25

400Wh

MD/LA

kg 22,3



REBEL 27,5"

EY627

MTB Alloy 27,5" internal cable routing

Rock Shox 30S 100mm

\$\frac{1}{8}\$ Shimano XT 10sp

(Shimano M396)

Schwalbe Rapid Rob 27'5"x2,25

500Wh

kg 21,2



REBEL 27,5" LITE **EY607**

MTB Alloy 27,5" internal cable routing

🕏 Shimano Deore 10sp

FSA 36T

↑ SR Suntour XCT HLO

Kenda Honey Badger 27'5"*2,25

400Wh

MD/LA

kg 21,8



REBEL JET LITE **EY517**

Sport Hybrid Alloy 28" internal cable routing

★ SR Suntour NEX HLO

7 Shimano Deore 10sp

FSA 38T

(Shimano M315)

Kenda K192 28"x1,75

400Wh

kg 21,8

MD/LA



REBEL CROSS LITE **EY507**

Sport Alloy 28" internal cable routing

↑ SR Suntour NEX HLO

Shimano Deore 10sp

(Shimano M315)

Kenda K192 28"x1,75

MD/LA

400Wh

kg 21,8

★ FSA 38T

■ FSA

E-BIKES NITRO

NITRO



LCD Center LCD Emotion

4

600Wh

44

500W Thru Axle

Up to 105 Km

45 Km/h

Upgrade kits

Bluetooth kit + Premium App GPS Tracker Winter Battery Cover



NITRO 29 " PRO **EN707**

MTB Alloy 29" internal cable routing Rock Shox 30S Remote 100mm

\$\frac{1}{8}\$ Shimano XT 10sp

Shimano Deore 48/36/26T

(Tektro Dorado

Schwalbe Smart Sam 29"x2,25

600Wh

111 MD

kg 23,5

NITRO RACE PRO **EN567**

Race Alloy 28" internal cable routing

Emotion Alloy

🕏 Shimano 105 11sp ₱ FSA CK-602 50/34T () Tektro Dorado C Schwalbe Marathon 700x25C

■ 600Wh

111 MD kg 21,3



NITRO JUMPER 27,5" PLUS PRO **EN907**

27,5" Plus internal cable routing FOX FLOAT DPS

FOX FLUAL D. C Performance FOX 34 FLOAT Rhythm 120mm 150R

Shimano Deore 48/36/26T

(Tektro Dorado

Schwalbe Nobby Nic 27,5PLUSx2,8

600Wh

111 MD

kg 24,3



NITRO 27,5" PRO **EN607** MTB Alloy 27,5" internal cable routing Rock Shox 30S Remote 100mm

7 Shimano XT 10sp

Shimano Deore 48/36/26T

(E) Tektro Dorado

Schwalbe Smart Sam 27,5"x2,25

4 600Wh

111 MD

kg 23,5



NITRO JET PRO **EN517**

Sport Hybrid Alloy 28" internal cable routing SR Suntour NCX–D LO Lite

🕏 Shimano XT 10sp Shimano Deore 48/36/26T

(Tektro Dorado

Schwalbe Marathon 700x38C

₫ 600Wh

kg 23,6

MD

NITRO E-BIKES 1



NITRO CROSS PRO EN507

Sport Alloy 28" internal cable routing SR Suntour NCX–D LO Lite

Shimano XT 10sp

Shimano Deore 48/36/26T

(E) Tektro Dorado
Schwalbe Marathon 700x38C

4 600Wh

111 MD

kg 23,6

BH.17

NITRO CITY PRO EN407

Sport Alloy 28" internal cable routing SR Suntour NCX–D LO Lite

Shimano XT 10sp


Shimano Deore 48/36/26T

(E) Tektro Dorado
Schwalbe Marathon 700x38C

4 600Wh

111 MD

kg 25,6





EV0

Center LCD Emotion Lateral LCD Emotion LCD 600Wh 500Wh 460Wh 400Wh 350W Thru Axle 350W 44

Up to 125 Km Up to 105 Km Up to 95 Km Up to 85 Km

25 Km/h

Upgrade kits

Bluetooth kit + Premium App GPS Tracker Winter Battery Cover Light cable Quick Realese Center LCD Emotion



EVO JUMPER 29" PRO

EV967

120 mm Full Suspension Alloy 29" internal cable routing Rock Shox Monarch

H

Shimano Deore 38/24T

MD

(E) Tektro E-Comp

kg 23,6

COMPATIBLE 27,5" PLUS

Schwalbe Racing Ralph 29"x2,25

Rock Shox 30S Remote

120mm 7 Shimano XT 10sp

600Wh





EVO JUMPER 27,5" **EV907**

120 mm Full Suspension Alloy 27'5" internal cable routing

Rock Shox Monarch Rock Shox 30S Remote

 Shimano Deore 40/28T (10) Tektro E-Comp

MD/LA kg 23,5

C Schwalbe Rapid Rob 27'5"x2,25 EVO 29" PRO **EV747** MTB Alloy 29"" internal cable routing FOX 32 FLOAT Performance 100mm

Shimano Deore 38/24T

\$\frac{1}{8}\$ Shimano XT 10sp

(E) Tektro E-Comp

Schwalbe Racing Ralph 29"x2,25

600Wh

MD/LA

kg 22,6

Shimano XT 10sp





EVO 29" **EV727**

MTB Alloy 29"" internal cable routing

Rock Shox 30S 100mm

Shimano XT 10sp Shimano Deore 38/24T (E) Tektro E-Comp

Schwalbe Rapid Rob 29"x2,25 500Wh

kg 23,1

MD/LA

EVO 29" LITE **EV707**

MTB Alloy 29"" internal cable routing

SR Suntour XCT HLO

🕏 Shimano Acera 8sp Suntour XR-172 42/32/22T


() Hydraulic Disc Brake

Kenda Honey Badger 29"*2,25 400Wh

MD/LA kg 23,1







E-BIKES EVO



EVO 27,5" PRO **EV647**

MTB Alloy 27,5" internal

cable routing FOX 32 FLOAT Performance 100mm

Shimano XT 10sp Shimano Deore 38/24T (D) Tektro E-Comp

Schwalbe Racing Ralph 27,5"x2,25

■ 600Wh

SM/MD/LA kg 22,3

EV627



EVO 27,5"

MTB Alloy 27,5" internal cable routing

Rock Shox 30S 100mm

7 Shimano XT 10sp Shimano Deore 38/24T (Tektro E-Comp

Schwalbe Rapid Rob 27'5"x2,25

■500Wh

kg 22,8

SM/MD/LA



EVO 27,5" LITE **EV607**

MTB Alloy 27,5" internal cable routing

SR Suntour XCT HLO

🕏 Shimano Acera 8sp

Suntour XR-172 42/32/22T

(D) Hydraulic Disc Brake

Kenda Honey Badger 27'5"*2,25

400Wh

MD/LA

kg 23,4

EVO RACE PRO **EV567**

Race Alloy 28" internal cable routing

★ Emotion Alloy

7 Shimano 105 11sp

(Tektro E-Comp

(Kenda K152 700x25C

4 600Wh

111 MD

kg 19,9

EVO JET PRO **EV557**

Sport Hybrid Alloy 28" internal cable routing SR Suntour NCX-D LO Lite

\$\frac{1}{8}\$ Shimano XT 10sp

Shimano Deore 48/36/26T

(E) Tektro E-Comp

Schwalbe Big Apple 28"x2,0

€ 600Wh

kg 24,3

MD/LA

EVO CROSS PRO **EV547**

Sport Alloy 28" internal cable routing SR Suntour NCX–D LO Lite H

🕏 Shimano XT 10sp

Shimano Deore 48/36/26T

(Tektro E-Comp SM/MD/LA

Schwalbe Big Apple 28"x2,0 **₫** 600Wh

kg 24,2

EVO E-BIKES 1



EVO JET

EV537

Sport Hybrid Alloy 28" internal cable routing

SR Suntour NEX HLO

7 Shimano Alivio 9sp

Shimano Alivio 48/36/26T

(E) Tektro E-Comp

C Schwalbe Big Apple 28"x2,0

⊈ 500Wh

MD/LA

kg 23,2





EVO CROSS

EVO CROSS LITE

EV507

EV527

Sport Alloy 28" internal cable routing

SR Suntour NEX HLO

Shimano Alivio 9sp

Shimano Alivio 48/36/26T

(E) Tektro E-Comp

Schwalbe Big Apple 28"x2,0

kg 23,3

■500Wh





EVO JET LITE **EV517**

Sport Hybrid Alloy 28" internal cable routing

SR Suntour NEX DS

Shimano Acera 8sp

SR Suntour XR-178 48/38/28T

() Hydraulic Disc Brake

Kenda K192 28"x1,75

400Wh

MD/LA

kg 23,2

Sport Alloy 28" internal cable routing

★ SR Suntour NEX DS

7 Shimano Acera 8sp

SR Suntour XR-178 48/38/28T

() Hydraulic Disc Brake

Kenda K192 28"x1,75

400Wh

MD/LA

kg 23,3



EVO CITY WAVE PRO **EV457**

City Wave Alloy 28" internal cable routing

SR Suntour CR8V HLO

\$\frac{1}{8}\$ Shimano XT 10sp

Shimano Deore 48/36/26T

(5) Magura Hydraulic HS-11 MD / LA

Schwalbe Marathon 700x38C

₫ 600Wh

kg 26,7



EVO CITY WAVE **EV437**

City Wave Alloy 28" internal cable routing

SR Suntour NEX HLO

🕏 Shimano Alivio 8sp

Shimano Altus 48/38/28T

(10) Hydraulic Disc Brake

Schwalbe Marathon 700x38C

⊈ 500Wh

MD/LA **kg** 26,3

E-BIKES EVO



EVO CITY

EV427

City Alloy 28" internal cable routing

SR Suntour NEX HLO

7 Shimano Alivio 8sp

Shimano Altus 48/38/28T

(D) Hydraulic Disc Brake

Schwalbe Marathon 700x38C

□ 500Wh

MD/LA

kg 26,3



EVO CITY WAVE LITE **EV417** City Wave Alloy 28" internal cable routing

Emotion Suspension

Shimano TX35 7sp

Suntour XR-178 48/38/28T

(V-Brake Alloy

(Kenda K192 28"x1,75

400Wh

kg 26,5

MD/LA



EVO STREET

EV337

Street Wave Alloy 26" internal cable routing

SR Suntour NEX HLO

Shimano Alivio 8sp

Shimano Altus 48/38/28T

() Hydraulic Disc Brake

Kenda K193 26"x1,75

500Wh

111 MD

kg 26,3



EVO ECO LITE **EV317** Street Wave Alloy 26" internal cable routing

Emotion Suspension

7 Shimano TX35 7sp

Suntour XR-178 48/38/28T

(V-Brake Alloy

Kenda K193 26"x1,75 kg 26,5

400Wh



AWD BIG BUD PRO

EW807

Fat Bike Alloy 26" internal cable routing

Emotion Double 42/32T

Emotion Hi-Ten

Shimano Acera 8sp

(Tektro E-Comp Emotion 26"x4,0

€ 600Wh

MD kg 28,7



AWD 29" LITE **EW707**

MTB Alloy 29"" internal cable routing

SR Suntour XCR-LO

7 Shimano XT 10sp

Shimano Deore 40/28T

(Tektro E-Comp

Schwalbe Rapid Rob 29"x2,25

400Wh

kg 26,2

MD

XENION E-BIKES 1

XENION

LCD LCD Intuvia 500Wh 400Wh 44 250W Up to 105 Km Up to 85 Km

25 Km/h

Upgrade kits



XENION JUMPER 27,5" EX927

120 mm Full Suspension Alloy 27'5"

ℬ 15T

(Shimano M615)

111 MD kg 21,2

FOX DPS Factory Remote FOX 32 FLOAT Performance Elite Remote 120mm

O CST C1435A 27,5"*2,10"

7 Shimano XT 11sp

500Wh





XENION 29"

EX727

MTB Alloy 29" internal cable routing

ℬ 15T

Rock Shox 30S 100mm 7 Shimano XT 10sp

500Wh

(Shimano M396) MD/LA

Michelin Country Grip'r 29"x2,10 kg 21,0

XENION JET

EX537

Sport Hybrid Alloy 28" internal cable routing

NSR Suntour NEX HLO

7 Shimano XT 10sp

500Wh

(S) Shimano M396

Rubena Antipuncture 700x35C

MD/LA

kg 21,2

分 18T



XENION CITY AVE LITE

City Wave Alloy 28" internal cable routing

★ SR Suntour NEX HLO

(Shimano M315) Rubena Antipuncture 700x35C

400Wh

MD/LA **kg** 23,9



XENION CROSS **EX527**

Sport Alloy 28" internal cable routing

ℬ 18T

↑ SR Suntour NEX HLO

\$\frac{1}{8}\$ Shimano XT 10sp

Rubena Antipuncture 700x35C **■** 500Wh

(Shimano M396)

kg 21,2

MD/LA

my**BH**warranty

Register your bike BH BIKES on our website: bhbikes.com during the first 30 days from the date of purchase, and you will receive on your new BH frame an extension to lifetime warranty*.

* See conditions in bhbikes.com

Extended warranties on the battery

2 year Warranty for the entire EMOTION range; components and battery.

Two extended warranties on the battery model:

- Extended warranty +1: 3 years for battery (€150 retail price).
 Extended warranty +2: 4 years for battery (€300 retail price).

EMOTION extended warranty conditions

- 1. The extended warranty specifies that it covers the BH EMOTION electric bicycle battery. It also states that it is governed by the laws of the country in which it is purchased and it may only be applied to bicycles acquired at an authorised European BH EMOTION retailer.
- 2. Batteries are guaranteed against manufacturing defects for a 3 year period (extended warranty +1) or 4 year period (extended warranty +2), starting from the date on which it is purchased by the buyer from the authorised BH **EMOTION** retailer.
- 3. This extended warranty does not mean that the battery will not malfunction or that it will be last for an indefinite period. It only implies that the battery is covered by the extended warranty, as set forth in the corresponding conditions.
- 4. This extended warranty only applies to the original buyer of a BH EMOTION electric bicycle and may not be transferred to any subsequent owners.

- 5. The bicycle and the battery should be taken to an authorised BH EMOTION retailer of the country in which it was purchased in order to make a warranty claim. The bicycle must be fully assembled and the original invoice must be provided along with the purchase date (it should be kept in a safe place).
- 6. Following an in-depth review of the battery in question, all warranties are subject to the decision made by our engineers concerning the nature of the fault.
- 7. This extended warranty will be cancelled and rendered ineffective, in the following instances:
- Improper use.
- Negligent use.
- When it is hired out.
- For use in competition of any kind.
- Repairs and/or maintenance.
- Changes and/or modifications.
- Accidents.

This extended warranty only covers batteries which were fully assembled when purchased and put together at an

authorised BH EMOTION retailer, or any other point of sale which has the express authorisation of BH EMOTION to market its bicycles.

- 8. This warranty does not cover:
 - Damage arising from faulty assembly and maintenance and/or the installation of pieces and accessories which are not compatible with the BH EMOTION bicycle.
 - Damage suffered by the original buyer of the bicycle, regardless of how the damage was caused.
 - Damage caused by the original buyer of the bicycle to third parties, regardless of how the damage was
 - Gradual deterioration of the battery in the course of its intended use.
- 9. All labour expenses related to the application of the warranty are to be met by the owner of the bicycle. During the period of application of the warranty, BH will repair all batteries or, if necessary, will replace the battery with another of the same model or the most similar model from those available.